






Series variation

Linear slide cylinder

LCM Series

● : Standard ○ : Option ■ : Not available

Variation	Model no. JIS symbol	Bore size (mm)	Standard stroke length (mm)				Option				Switch	Page
			5	10	15	20	With buffer	With magnet	Magnet + with switch rail	Dowel pin attached		
			●	●	●	●	B	M	F	J*		
Double acting single rod type		φ 4.5	●	●	■	■						1770
		φ 6	●	●	●	■	○	○	○	○	○	
		φ 8	●	●	●	●						
Double acting stroke adjustable type (extended)		φ 4.5	●	●	■	■						1780
		φ 6	●	●	●	■	○	○	○	○	○	
		φ 8	●	●	●	●						
Double acting stroke adjustable type (extended/retracted)		φ 4.5	●	●	■	■						1788
		φ 6	●	●	●	■	○	○	○	○	○	
		φ 8	●	●	●	●						
Double acting side installation type		φ 4.5	●	●	■	■						1796
		φ 6	●	●	●	■	○	○	○	○	○	
		φ 8	●	●	●	●						
Double acting single rod type clean room specifications		φ 4.5	●	●	■	■	■					1808
		φ 6	●	●	●	■		○	○	○	○	
		φ 8	●	●	●	●						

Note: Custom stroke length is not available.

- SCP*2
- CMK2
- CMA2
- SCM
- SCG
- SCA2
- SCS
- CKV2
- CA/OV2
- SSD
- CAT
- MDC2
- MVC
- SMD2
- MSD*
- FC*
- STK
- ULK*
- JSK/M2
- JSG
- JSC3
- USSD
- USC
- JSB3
- LMB
- STG
- STS/L
- LCS
- LCG
- LCM**
- LCT
- LCY
- STR2
- UCA2
- HCM
- HCA
- SRL2
- SRG
- SRM
- SRT
- MRL2
- MRG2
- SM-25
- CAC3
- UCAC
- RCC2
- MFC
- SHC
- GLC
- Ending

- SCP*2
- CMK2
- CMA2
- SCM
- SCG
- SCA2
- SCS
- CKV2
- CA/OV2
- SSD
- CAT
- MDC2
- MVC
- SMD2
- MSD*
- FC*
- STK
- ULK*
- JSK/M2
- JSG
- JSC3
- USSD
- USC
- JSB3
- LMB
- STG
- STS/L
- LCS
- LCG
- LCM**
- LCT
- LCY
- STR2
- UCA2
- HCM
- HCA
- SRL2
- SRG
- SRM
- SRT
- MRL2
- MRG2
- SM-25
- CAC3
- UCAC
- RCC2
- MFC
- SHC
- GLC
- Ending

Linear slide cylinder
Combined functions