

# NDP-5 SERIES

Maximum Capacity 11,7 l/min (3,1 GPM)  
 Port Size 1/4" (5 mm)



## NDP-5 Polypropylene

Dimensions:  
 156 mm W x 152 mm H  
 Net Wt.: 1,36 kg  
 Shipping Wt.: 1,81 kg

## NDP-5 Groundable Kynar®

Dimensions:  
 156 mm W x 152 mm H  
 Net Wt.: 1,67 kg  
 Shipping Wt.: 2,1 kg



## NDP-5 Groundable Acetal

Dimensions:  
 156 mm W x 152 mm H  
 Net Wt.: 1,67 kg  
 Shipping Wt.: 2,1 kg



## NDP-5 Stainless Steel

Dimensions:  
 155 mm W x 149 mm H  
 Net Wt.: 2,68 kg  
 Shipping Wt.: 3,1 kg



## NDP-5 Aluminum

Dimensions:  
 155 mm W x 149 mm H  
 Net Wt.: 1,5 kg  
 Shipping Wt.: 1,9 kg

## NDP-5 SPECIFICATIONS

### Port Dimensions

Intake & discharge connection:	1/4" 5 mm Female Rc
Air inlet (incl. ball valve):	1/4" 5 mm Female Rc
Air exhaust (internal silencer):	3/8" 10 mm Female Rc

### Air Supply Pressure (All Models)

1,4 – 7 Bar (0,14 – 0,7 MPa)

### Discharge Volume Per Cycle

29 cc

### Maximum Cycles Per Minute: 400

### Maximum Dry Suction Lift: 1,5 m

### Air Motor

Standard: Ryton® air motor

### Model Number Nomenclature

Polypropylene (PPG)	NDP-5FPT
Groundable Kynar® (PVDF)	NDP-5FVT
Groundable Acetal (POM)	NDP-5FDT
Aluminum (ADC-12)	NDP-5FAT
Stainless Steel (316)	NDP-5FST

### NDP-5 serie Performance Curve

